



द्वारा : स्पीड पोस्ट/हाथों – हाथ



भा. कृ. अनु. प. – केन्द्रीय शुष्क क्षेत्र अनुसंधान संस्थान  
ICAR - Central Arid Zone Research Institute  
जोधपुर (राजस्थान) 342 003 / Jodhpur (Rajasthan) 342 003  
Website: www.cazri.res.in, Email: director.cazri@icar.gov.in  
Phone No. 0291 – 2786584 / FAX: 0291 – 2788706



F. No. 29(1)/2019-2020/Admn.IV

Dated : 02.08.2019

To

M/s.....  
.....  
.....  
.....

Sub: Inviting Quotations for Purchase of Digital Camera.

Dear Sir(s),

You are requested to kindly quote your lowest rates on the letter head of your firm with your all terms & condition keeping the following conditions in view, in respect of the articles as mentioned in the Schedule to Tender.

1. No advance payment will be made. However, the payment is normally made within 30 days from the date of receipt of material in good condition as per order.
2. Payment will be made by mode of e-payment to the supplier/firm after satisfactory supply of ordered material and receipt of pre-receipt.
3. The quantity proposed in the quotation may be increased or decreased at the discretion of the authority while placing the order.
4. Quotations not found according to specification will be rejected/not considered.
5. The firm should supply the printed literature, operational manual etc., if applicable. The firm should also supply a copy of the authorised dealership certificate of the item, if applicable.
6. Quotations should remain valid for 6 months from the date of quotation.
7. The rate should be on F.O.R. ICAR-CAZRI, Jodhpur basis for indigenous items.
8. The firm should indicate PAN/TIN/GST as per Govt. Rules.
9. The Rates quoted should **be clearly be indicated in figure as well as in words.** While quoting the rates, it may be clearly indicated whether the items are inclusive or exclusive of GST, Excise Duty, Custom Duty, Octroi etc. either in terms of percentage or in absolute term.
10. Delivery will have to be made normally within 30 days from the date of issue of our order or as mentioned in the supply order unless such extension is allowed by the Institute **failing which suitable penalty as indicated in the supply order will be imposed.**
11. The quotation may be sent to the office by courier/Regd. Post/Speed Post in sealed cover superscribed with **“Quotation for Purchase of Digital Camera”** due date 17.08.2019 and the same must be reach to this Office on or before **17.08.2019 upto 3.00 PM** failing which it will not be considered. The quotation should be dropped in the Tender Box placed in the Store Section (with A.A.O. IV). The Quotation will be opened on the very same i.e. on 17.08.2019 at 3.30 PM in presence of the representative of the firm if they desire to attend.
12. In case of any disputes, the decision of the Director, CAZRI, Jodhpur shall be binding on the part of the contractor/supplier.
13. Director, CAZRI, Jodhpur reserves the right to accept or reject any or all the quotation without assigning any reason.
14. All bids must be accompanied by a bid security/Earnest money deposit (EMD) @ 2% of the estimated value of the item, **if the cost of the item is more than Rs. 1.00 lac** in the form of a Demand Draft on a scheduled commercial bank in India, in favour of **ICAR Unit – CAZRI, Jodhpur.** Without EMD as above, quotation will not be considered (**Item less than Rs. 1.00 lac need not require EMD.**) If the firm is registered with National small Industries Corporation (NSIC) there is no need to submit EMD (Bid Security).
15. No part supply will be allowed.
16. The items required is for the ICAR-CAZRI, Jodhpur and therefore, supply will have to be made accordingly.

Administrative Officer  
for Director**Schedule to Tender**

S.No.	Name of the items	Broad specification	Qty.	Place of supply
1.	Digital SLR Camera	<ul style="list-style-type: none"> <li>➤ <b>Model:</b> DSLR D500 (Size: 5.8 x 4.5 x 3.2 in)</li> <li>➤ <b>Image Sensor:</b> CMOS, 20.9-megapixel, APS-C sensor format, size 23.50mm x 15.70mm (368.95mm<sup>2</sup>)</li> <li>➤ <b>Lens Mounting:</b> Detachable; F mount</li> <li>➤ <b>Focus:</b> Auto/Manual; Manual Focus, OVF: Advanced Multi-CAM 20K autofocus sensor module with TTL phase detection fine-tuning, and 153 focus points (including 99 cross-type sensors and 15 sensors that support f/8), of which 55 (35 cross-type sensors and 9 f/8 sensors) are available for selection; Contrast-detect AF in Live View mode</li> <li>➤ <b>Viewfinder:</b> Optical / LCD, SLR type: eye-level pentaprism, 100% coverage, 1.0x magnification (~0.67x 35mm eq.), 16mm eyepoint, -2 to +1 diopter, monitor size</li> <li>➤ <b>Display:</b> Eye-level Viewfinder, Rear Display (size 3.2 in), Touch screen, Articulating Screen</li> <li>➤ <b>Exposure:</b> ISO 100-51200, Auto, ISO 100 - 51200, expandable to Lo-1 ISO 50 to Hi-5 ISO 1,638,400, 1/8000 - 30 sec shutter speed</li> <li>➤ <b>Image Storage:</b> XQD / SD / SDHC / SDXC, Dual Card Slots, RAW Capture Support, UHS Support</li> <li>➤ <b>Connectivity:</b> Built-In Wi-Fi, NFC, Bluetooth, Microphone Jack, Headphone Jack</li> <li>➤ <b>Performance Timing:</b> &lt;0.3 Cycle time for JPEG shooting in single shot mode (seconds per frame, max resolution) and 10.2 JPEG &amp; RAW shooting speed in burst mode (fps, max resolution), 200 Buffer size for JPEG/RAW shooting in burst mode (frames, max resolution) etc</li> <li>➤ <b>Power:</b> Lithium-ion rechargeable, Dedicated Battery Charger Included</li> <li>➤ <b>Software:</b> ViewNX-i, ViewNX-Movie Editor, Capture NX-D, Nikon Transfer 2, Picture Control Utility 2 downloads; OS computability: Windows 7/8/10, Mac OS X 10.9.5-10.11.5</li> </ul>	01 No.	ICAR-CAZRI, Jodhpur
	Lens	<ul style="list-style-type: none"> <li>➤ AF-S DX 18-300mm f/3.5-5.6G ED VR</li> <li>➤ <b>Maximum format size:</b> DX</li> <li>➤ <b>Focal length:</b> 18-300mm,</li> <li>➤ <b>35mm equivalent focal length:</b> 27-450mm</li> <li>➤ <b>Diagonal Angle of view (APS-C):</b> 76° - 5° 20'</li> <li>➤ <b>Maximum aperture:</b> F3.5-5.6, <b>Minimum aperture:</b> F22-32</li> <li>➤ <b>Lens Construction:</b> 19 elements / 14 groups, 3 ED glass elements, 3 aspherical elements</li> <li>➤ <b>Number of diaphragm blades:</b> 9, rounded</li> <li>➤ <b>Minimum focus:</b> 0.45m</li> <li>➤ <b>Maximum magnification:</b> 0.32x</li> <li>➤ <b>AF motor type:</b> Silent Wave Motor (Ring-type ultrasonic), Full-time manual focus (M/A mode)</li> <li>➤ <b>Focus method:</b> Internal, <b>Zoom method:</b> Rotary, extending barrel</li> <li>➤ <b>Image stabilization:</b> Yes; 4 stops claimed benefit, 'Active' mode</li> <li>➤ <b>Filter thread:</b> 77mm, Does not rotate on focus</li> </ul>	50,000.00	

		<ul style="list-style-type: none"> <li>➤ <b>Supplied accessories:</b> Front and rear caps, HB-58 Petal-type Hood (variable in different countries)</li> <li>➤ <b>Weight:</b> 830 g (29.3 oz)</li> <li>➤ <b>Dimensions:</b> 83 mm diameter x 120 mm length, (3.3 x 4.7 in)</li> <li>➤ <b>Lens Mounting:</b> Detachable; F mount</li> </ul>		
	Flash	<ul style="list-style-type: none"> <li>➤ SB 500 Speed Light</li> <li>➤ <b>Guide Number:</b> 24m/78.7ft. (at ISO 100)</li> <li>➤ <b>Lens Coverage:</b> 24 mm lens (FX format) or 16 mm lens (DX format)</li> <li>➤ <b>Bounce Function (Tilt):</b> Flash head tilts up to 90° with click-stops at 0°, 60°, 75°, 90°.</li> <li>➤ <b>Bounce Function (Rotate):</b> Flash head rotates horizontally 180° to the left and right with click-stops at 0°, 30°, 60°, 75°, 90°, 120°, 150°, 180°</li> <li>➤ <b>Approx. Dimensions (Width x Height x Depth):</b> 2.6 in. (67 mm) x 4.5 (114.5 mm) x 2.8 in. (70.8 mm)</li> <li>➤ <b>Approx. Weight (Without Batteries):</b> 8 oz. (226 g)</li> </ul>	15,000.00	

Administrative Officer  
for Director